

Spec Sheet

4 Port Native PCI Express RS232 Serial Adapter Card with 16550 UART

StarTech ID: PEX4S553



The PEX4S553 4-Port Native PCI Express RS232 Serial Adapter Card with 16550 UART lets you add 4 RS232 (DB9) serial ports, using a single PCI Express expansion slot.

Based on a native single-chip design, this 4-port serial adapter card allows you to harness the full capability offered by PCI Express (PCIe), while reducing the load applied to the CPU by as much as 48% over conventional bridge-chip serial cards.

The RS232 Serial Adapter Card includes 4 half-height/low-profile brackets, allowing the card to be installed into almost any PC case, regardless of form factor.

Backed by a StarTech.com Lifetime warranty and free lifetime technical support.

Applications

- POS retail applications in grocery stores, and any other retail store to control keyboards, cash drawers, receipt printers, card readers / card swipes, scales, and elevated displays on poles
- Bank teller workstations in either full profile or low profile versions to control their serial devices such as cash drawers, card readers / card swipes, printers, keypads / pinpads, pen pads
- Self-service automated machines and kiosks to control serial devices such as scales, touchscreens, magnetic card readers, bar code scanners, receipt printers, label printers
- Standard ATM automated teller machines to control keypads, receipt printer, card readers / card swipes, touchscreen LCD's, camera control, etc.
- Used to control multiple surveillance / security cameras in a parking structure, office building, etc.





Features

- Four high speed RS232 serial ports, with support for data transfer rates up to 128000bps
- 256-byte deep FIFO per transmitter and receiver
- Native single-Chip, single lane PCI Express
- Includes half-height/low profile mounting brackets
- Built-in 16C450/550 compatible UART
- Compliant with PCI Express Base Specification 1.1

StarTechcom

Hard-to-find made easy®

Technical Specifications

Warranty Lifetime Bus Type PCI Express Card Type Standard Profile (LP bracket incl.) Chipset ID ASIX/MosChip - MCS9904CV-AA Interface Serial Port Style Integrated on Card 4 Ports Data Bits 5, 6, 7, 8 FIFO 256 bytes Max Baud Rate 128 Kbps MTBF 26,280 Hours Parity 5, 6, 7, 8 RS-232 Serial Protocol Connector Type(s) 1 - PCI Express x1 Male External Ports 4 - DB-9 (9 pin; D-Sub) Male Microsoft WHQL Certified Yes OS Compatibility Windows® 10 (32/64), 8 / 8.1 (32/64), 7 (32/64), Vista (32/64), XP (32/64) Windows Server® 2012, 2008 R2, 2003 Mac OS® 10.10 Linux Humidity 5~85% RH Operating Temperature 0°C to 50°C (32°F to 122°F) Storage Temperature -20°C to 60°C (4°F to 140°F) Color Green Product Height 0.7 in [19 mm] Product Length 4.7 in [120 mm] Product Weight 2.8 oz [80 g] Product Width 5.1 in [130 mm] Shipping (Package) Weight 0.5 lb [0.2 kg] Included in Package 1 - 4 Port PCI-Express RS-232 Serial Card 1 - Bracket with 2 DB9 male ports Included in Package 4 - Low Profile Brackets Included in Package 1 - Driver CD Included in Package 1 - Instruction Manual Included in Package

Spec Sheet



Certifications, Reports and Compatibility









Spec Sheet

www.startech.com 1 800 265 1844