## PT9051SL/BL

### GE Profile<sup>™</sup> Series 30 in. Built-In Single Convection Wall Oven

### **DIMENSIONS AND INSTALLATION INFORMATION (IN INCHES)**

# MOST 30" WALL CABINETS CAN BE USED WITH THIS UNIT.

**NOTE:** These ovens are not approved for stackable installations. Cabinets installed adjacent to wall ovens must have an adhesion spec of at least a 194°F temperature rating.

Door handle protrudes 3" from door face. Cabinets and drawers on adjacent  $45^{\circ}$  and  $90^{\circ}$  walls should be placed to avoid interference with the handle.

Electric wall ovens are not approved for installation with a plug and receptacle. They must be hard wired in accordance with installation instructions.

#### **INSTALLATION INFORMATION:**


Before installing, consult installation instructions packed with product for current dimensional data.


Side-by-side installations rerquire at least 2" between cutouts.

KW RATING	
240V	4.5
208V	3.4
BREAKER SIZE	
240V	20 Amps
208V	20 Amps

**GE APPLIANCES** 


uts.	PT9051
Cabinet	30"
A - Overlap of oven at top of cutout	1 1/4"
B - Overlap of oven other side of edge of cutout	11/16"
C - Overlap of oven at bottom of cutout	1 1/4"
Oven	
D - Install depth	27 3/16"
E - Overall height with trim	28 3/8"
F - Overall width	29 3/4"






Dimension and installation information are shown in inches.

#### **INSTALLATION BELOW A COOKTOP**






2 x 4 or equivalent runners level with bottom of cutout and flush with sides of cutout or solid bottom floor











## PT9051SL/BL

### GE Profile<sup>™</sup> Series 30 in. Built-In Single Convection Wall Oven

### OPTIONAL UNDERCOUNTER DIMENSIONS AND INSTALLATION INFORMATION

**NOTE:** 36" ribbon cooktop are approved for use over GE 30" single wall ovens and warming drawers. 30" ribbon cooktops are approved for use over 30" and GE 27" single wall ovens and warming drawers. Refer to cooktop and wall oven installation information packed with products for current dimensional data.


**NOTE:** Door handle protrudes 3" from door face. Cabinets and drawers on adjacent  $45^{\circ}$  and  $90^{\circ}$  walls should be placed to avoid interference with the handle.

**INSTALLATION INFORMATION:** Before installing, consult installation instructions packed with products for current dimensional data and for alternate installation options.

ELECTRIC WALL OVENS ARE NOT APPROVED FOR INSTALLATION WITH A PLUG AND RECEPTACLE. THEY MUST BE HARD WIRED IN ACCORDANCE WITH INSTALLATION INSTRUCTIONS.

Dimension and installation information are shown in inches.

Gas or electric cooktops may be installed over this oven. See cooktop installation instructions for cutout size. See label on top of oven for approved cooktop models.





## PT9051SL/BL

## GE Profile<sup>™</sup> Series 30 in. Built-In Single Convection Wall Oven

#### **FEATURES AND BENEFITS**

Brilliant Touch 7" Display – A bright, interactive touch screen makes it fun and easy to program the oven

Precision Cooking Modes – Select from preprogrammed cooking modes to get perfect results every time

True European Convection with Direct Air – Bakes evenly as warm air blows from the top in and around bakeware

WiFi Connect – Wirelessly control oven functions from your smartphone

Ten-pass bake element – Even baking is assured with heat that covers more surface area

Ten-pass dual broil element – Large and small dishes brown evenly with two, full-coverage elements

Self-clean, heavy-duty roller rack – Easily access items with a rack that glides smoothly

Progressive halogen oven lighting – See what you're baking with lights that slowly illuminate the oven

Self-clean with Steam Clean option - Clean your oven the way you want

Model PT9051SLSS - Stainless steel

Model PT9051BLTS - Black stainless

### **GUARANTEED FIT**

Replacing a similar wall oven from GE or another brand? GE wall ovens are guaranteed for an exact fit to make replacement easy

Visit geappliances.com for more info



