## TABLE OF CONTENTS

Warranty2	Maintenance13-16
Product Specifications2	Service and Adjustments17-18
Safety Rules2-4	Storage
Assembly / Pre-Operation6-7	Troubleshooting19-20
Operation8-12	
Maintenance Schedule13	Sears ServiceBack Cover

### WARRANTY

#### **CRAFTSMAN 2-YEAR FULL WARRANTY**

For TWO YEARS from the date of purchase, this product is warranted against any defects in material or workmanship. Defective product will receive free repair or replacement if repair is unavailable.

For warranty coverage details to obtain free repair or replacement, visit the web page: www.craftsman.com/warranty

# This warranty covers ONLY defects in material and workmanship. Warranty coverage does NOT include:

- Expendable parts that can wear out from normal use within the warranty period, such as blades, blade adapters, belts, filters or spark plugs.
- Product damage resulting from user attempts at product modification or repair or caused by product accessories.
- Repairs necessary because of accident or failure to operate or maintain this product according to all supplied instructions.
- Preventative maintenance, or repairs necessary due to improper fuel mixture, contaminated or stale fuel.

This warranty is void if this product is ever used while providing commercial services or if rented to another person.

This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Sears Brands Management Corporation, Hoffman Estates, IL 60179

## **PRODUCT SPECIFICATIONS**

Serial Number:

Date of Purchase:	
Gasoline Capacity / Type:	0.8 Quarts (Unleaded Regular)
Oil Type (API SJ–SN):	SAE 30 (above 32°F); SAE 5W-30 (below 32°F)
Oil Capacity:	15.5 Ounces
Spark Plug (Gap: .020")	Champion RC12YX
Blade Bolt Torque:	35–40 ft. lbs.

 The model and serial numbers will be found on a decal on the rear of the lawn mower housing. Record both serial number and date of purchase in space provided above.

## SAFETY RULES

**IMPORTANT:** This cutting machine is capable of amputating hands and feet and throwing objects. Failure to observe the following safety instructions could result in serious injury or death. A Look for this symbol to point out important safety precautions. It means CAUTION!!! BECOME ALERT!!!

YOUR SAFETY IS INVOLVED.

A WARNING: In order to prevent accidental starting when setting up, transporting, adjusting or making repairs, always disconnect spark plug wire and place wire where it cannot come in contact with plug.

KEY NO.	PART NO.	DESCRIPTION	KEY NO.	PART NO.	DESCRIPTION	
404	690272	Washer (Governor Crank)	850	100106	Sealant-Silicone	
445	593260	Filter-Air Cleaner Cartridge	868	590534	Seal-Valve	
455	593960	Cup-Flywheel	875	595661	Base-Air Cleaner	
493	593330	Bracket-Mounting	914	591103	Screw (Rocker Cover)	
		(Carburetor)	922	692135	Spring-Brake	
505	793515	Nut (Governor Control Lever)	923	691487	Brake	
523	796503	Dipstick	951	591104	Lever-Choke	
524	691876	Seal-Dipstick Tube	957	591003	Cap-Fuel	
562	793514	Bolt	968	595658	Cover-Air Cleaner	
		(Governor Control Lever)	971	590552	Screw (Air Cleaner Base	
598	592587	Shim-End Play (Crankshaft)			to Carburetor)	
		(Used After Date Code	972	590568	Fuel-Tank	
		15100100)	975	594632	Bowl-Float	
	593291	Shim-End Play (Crankshaft)	1022	595341	Gasket-Rocker Cover	
		(Used Before Date Code	1023	590513	Cover-Rocker	
		15100200)	1026	590515	Rod-Push	
601	791850	Clamp-Hose (Green)			(Intake and Exhaust)	
608	593959	Starter-Rewind	1029	590526	Arm-Rocker (Exhaust)	
613	590562	Screw (Muffler)		590527	Arm-Rocker (Intake)	
615	690340	Retainer-Governor Shaft	1036		Label-Emissions (Available	
616	590516	Crank-Governor			From A Briggs & Stratton	
617	270344s	Seal-O Ring (Intake Manifold)			Authorized Dealer)	
621	692310	Switch-Stop	1127	590554	Screw (Float Bowl	
623	799581	Seal-O Ring	1000	500500	to Carburetor Body)	
005	000070	(Carburetor Spacer)	1238	590562	Screw (Carburetor Spacer)	
635	692076	Boot-Spark Plug	1000	007104	(M5 x 17mm)	
668	590546	Spacer (Flywheel)	1263 1264	697124 793453	Reed-Breather	
718 724	690959 697478	Pin-Locating Retainer-Seal	1204	793453 N/A	Screw (Breather Reed) Replacement Engine	
724	594752		1329		Repair Manual	
729 741	594752 594105	Clip-Wire Gear-Timing		N/A 398067	Spark Arrester	
741	691146	Screw (Brake) (#10-32 x .8)		390007	(available accessory)	
745 745A	690859	Screw (Brake) (#10-32 x .8) Screw (Brake) (#10-32 x .5)			(available accessory)	
745A 770	595355	Kit-Rewind/Blower Housing	Carburetor Overhaul Kit Key No. 121			
830	590536	Stud-Rocker Arm	Carburetor Overnaul Kit Key NO. 121			
836	690661	Screw (Muffler Guard)	Engine Gasket Set Key No. 358			
000	030001	(#8-18 x .4)	Ligine Gasker Ser Key NO. 330			
842	691031	Seal-O Ring (Dipstick)	NOTE: All component dimensions given in U.S.			
847	590572	Dipstick/Tube Assembly		inches.	1  inch = 25.4  mm	
577	000012	Dipolion/ Tube Assembly		incrico.	1 11011 – 23.4 11111	