

# Kenmore

## Operating conditions :

Flow rate : 0.5 GPM (1.9LPM)  
Pressure : 30 – 125 psi (207 – 862 kPa)  
Temperature : 34 – 100 °F (1 – 38 °C)  
Service life : 6 Months  
Capacity : 300 Gallons (1,136 Liters)  
Function : Chemical/Mechanical Reduction



System tested and certified by NSF international against NSF / ANSI standard 42 for the reduction of Chlorine, Taste and Odor and Particulate Class III.

## Installation Instructions :

1. Shut off water supply
  2. Rotate the old filter counter clockwise 1/4 turn and pull it out.
  3. Insert the new filter into the filter head and rotate clockwise 1/4 turn.
  4. Turn on the water and check for leaks. If leaks occur, repeat step 1,2,3,4.
- If leaks persist, discontinue use and call your supporting dealer
5. Flush filter for 5 minutes before use.

## Notice :

1. Do not with water that microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.
2. For cold water only.
3. Replace the filter every 6 months and contact your local dealer or place where you purchase

Replacement cartridge No.: DW2042FR-09  
For Use In System Model No.: DW2042FR-09

**For replacement, contact your local dealer or place where you purchase**  
Manufactured by Micro Filter Co.,Ltd 162-1, Sansu, Deoksan, Jinchun, Chungbuk  
Made in Korea

