Revision date: 2020/04/21

Version: 1.2

## **Section I. Identification**

SQ Non-Chlorinated Brake Cleaner

### 1.1 Product identifier

SQ Non-Chlorinated Brake Cleaner Product name

Product number 0200 **Brand** SQ

## 1.2 Recommended use of the chemical and restrictions on use

Use: automotive car care, brake cleaner.

## 1.3 Suppliers detail:

Name Sicamu, Inc Address 1066 Strong Rd Quincy, FL 32351

(850) 270-6283

Telephone

1.4 Emergency phone number (s) 1 (800) 424-9300

## Section II. Hazard identification

## 2.1 Classification of the substance or mixture

Flammable Aerosol	2	H225
Gases under Pressure (compressed gas)		H280
Aspiration Hazard	1	H304
Skin Corr./Irrit	2	H315
Serious eye damage	1	H318
Serious eye irritation	2A	H319
May cause drowsiness or dizziness	3	H336
Suspected damage fertility of the unborn child	2	H361
Specific target organ toxicity, single exposure	3	H336
May cause damage to organs (central nervous		
system, liver, heart)through prolonged or		
repeated exposure	2	H373
Short term (acute) aquatic hazard	1	H400
Harmful to aquatic life	3	H402
Long-term (chronic) aquatic hazard	1	H410

### 2.2 Label elements

Page 2/16

Revision date: 2020/04/21

Version: 1.2







GHS07



GHS02 GHS04 Signal word (GHS-US)

Danger

Pictogram:

Flammable.

Content under pressure.

Health Hazard.

### **Hazard Statement:**

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapor.
H280	Contains gas under pressure. May explode if heated.
H304	May be fatal if swallowed and enters in airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

## Precautionary Statements (Prevention)

P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211	Do not spray on an open flame or other ignition source.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P251	Pressurized container. Do not pierce or burn, even after used.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash hands thoroughly after handling
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves and eye/face protection.

## Precautionary Statements (Response)

P302+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses if present and easy to do. Continue rinsing.

Page 3/16

Revision date: 2020/04/21

Version: 1.2

P301+P310 Immediately call a POISON CENTER or doctor/physician.

P301+P312+P330 IF SWALLOWED: call a POISON CENTER if you feel unwell. Rinse mouth.

P303+P352 IF ON SKIN (or hair): Wash with plenty of soap and water.

P304+P340+P312 If INHALED: remove person to fresh air and keep comfortable for breathing. Call

POISON CENTER/doctor if you feel unwell.

P331 Do not induce vomiting.

P332+P313 If skin irritation occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: use dry sand, dry chemical or alcohol-resistant foam to

extinguish.

P391 Collect spillage.

Precautionary Statements (Storage):

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection point.

### 2.3 Hazards not otherwise classified.

No specific damages known if the regulations/notes for storage and handling are considered.

# Section III. Composition/Information on Ingredients

<b>CAS Number</b>	Weight %	<b>Chemical Name</b>
67-64-1	40-60 %	2-propanone
108-88-3	15-20 %	Methylbenzene
142-82-5	15-20%	Heptane
67-56-1	10-15 %	Methyl Alcohol
124-38-9	1-5 %	Carbon Dioxide

## Section IV. First aid measures

4.1 Description of first aid measures

**General advice:** 

Page 4/16

Revision date: 2020/04/21

Version: 1.2

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled:

If breathing move person into fresh air. If not breathing, perform artificial respiration. If adverse health effects develop seek medical attention.

#### If on skin:

After contact with skin wash immediately with plenty of water. If adverse health effects develop seek medical attention.

#### If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open. Seek medical attention.

#### If swallowed:

Do not induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs naturally keep airways clear. Seek medical attention.

## 4.2 Most important symptoms and effects, both acute and delayed:

**Eyes:** irritation. Symptoms may include discomfort or pain, excess blinking, and tear production, with possible redness and swelling.

Inhalation: can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

**Skin:** may cause irritation, symptoms may include redness and drying of the skin.

**Ingestion:** may be fatal if swallowed. This product may enter airways and aspirated into the lungs causing chemical pneumonitis. It may also cause stomachal distress and vomiting.

### 4.3 Indication of any immediate medical attention and special treatment needed:

Note to physician

Treat according to symptoms (decontamination, vital functions), no

known specific antidote.

# Section V. Firefighting measures

### 5.1 Extinguishing media:

Suitable extinguishing media:

Carbon dioxide, dry chemicals, halons of foam.

Unsuitable extinguishing media:

Do not use water jet.

#### **5.2** Special hazards arising from the substance or mixture:

Fire hazard: flammable aerosol, products of combustion may include, and are not limited to:

carbon dioxide, carbon monoxide.

Sicamu, Inc.
Safety Data Sheet
SQ Non-Chlorinated Brake Cleaner

Page 5/16

Revision date: 2020/04/21

Version: 1.2

Explosion hazard: heat may build pressure, rupturing closed containers, spreading fire and

increasing risk of burns and injuries.

Reactivity: no dangerous reactions under normal circumstances.

5.3 Advice for firefighters:

Firefighting instructions: DO NOT FIGHT FIRE when fire reaches explosiveness. Evacuate area, use

caution when fighting any chemical fire.

Protection during firefighting: keep upwind of fire. Wear full firefighting turn-out gear and respiratory

protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray

to keep fire-exposed containers cool.

5.4 Further information:

In case of fire: evacuate area. Fight fire remotely due to the risk of explosion. Use water spray to cool unopened containers.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

## Section VI. Accidental release measures

### 6.1 Personal precautions, protective equipment, and emergency procedures:

Use personal protective equipment. Avoid breathing vapors, mist, or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personal to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

### **6.2 Environmental precautions:**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Discharge into the environment must be avoided.

## 6.3 Methods and material for containment and cleaning up:

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations.

### 6.4 Reference to other sections:

For personal protection see Section 8.

For disposal considerations see Section 13.

# Section VII. Handling and storage

### 7.1 Precautions for safe handling:

Page 6/16

Revision date: 2020/04/21

Version: 1.2

Do not spray on an open flame or other ignition sources. keep away from ignition sources. No smoking. Use non-sparking tools. Use explosion-proof equipment. Take precautionary measures against static discharge. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas, fumes, vapor or spray. When using do not eat, drink, or smoke. Use only outdoors in a well-ventilated area. Do not pierce or burn, even after use.

Hygiene measures: launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

## 7.2 Conditions for safe storage, including any incompatibilities:

Store in a dry and well-ventilated place. Keep locked and out of reach of children. Do not expose to temperatures exceeding 40°C/104°F. Store away from direct sunlight or other heat sources. keep in fire-proof place.

Storage: sore in a well-ventilated place, out of the reach of children and pets.

### 7.3 Specific end uses:

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

# Section VIII. Exposure controls/personal protection

## 8.1 Components with occupational exposure limits:

2 Propanone CAS # 67-		S # 67-64-1
ACGIH	ACGIH TLV (ppm)	500 ppm
ACGIH	ACGIH STEL (ppm)	750 pp,
OSHA	OSHA PEL (TWA) (mg/m³)	1,000 mg/m <sup>3</sup>

Methylbenzene		CAS# 108-88-3
ACGIH	ACGIH TWA (ppm)	20 ppm
OSHA	OSHA PEL (TWA) (ppm)	200 pm
OSHA	OSHA PEL (ppm)	300 ppm

Heptane CAS #	<i>‡</i> 142-82-5
---------------	-------------------

TWA	85 ppm 350 mg/m <sup>3</sup>	USA NIOSH Recommended Exposure Limits.
С	440 ppm 1,800 mg/m <sup>3</sup>	USA NIOSH Recommended Exposure limits.

15 minutes ceiling value.

TWA 500 ppm 2,000 mg/m<sup>3</sup> USA Occupational Exposure Limits (OSHA) Table Z-1 Limits for

air contaminants.

PEL 400 ppm 1,600 mg/m<sup>3</sup> California permissible exposure limit for chemical contaminants

(Title 8, Article 107)

Page 7/16

Revision date: 2020/04/21

Version: 1.2

STEL 500 ppm 2,600 mg/m³ California permissible exposure limit for chemical contaminants

(Title 8, Article 107)

TWA 400 ppm USA ACGIH Threshold Limit Values (TLV)

Central Nervous System impairment Upper Respiratory Tract irritation

STEL 500 ppm USA ACGIH Threshold Limit Values (TLV)

Methyl AlcoholCAS # 67-56-1ACGIHACGIH TWA (ppm)200 ppmACGIHACGIH STEL (ppm)250 ppmNIOSHNIOSH TWA (mg/m³)325 mg/m³NIOSHNIOSH STEL (ppm)250 ppm

 Carbon Dioxide
 CAS # 124-38-9

 ACGIH
 ACGIH TWA (ppm)
 5,000 ppm

 ACGIH
 ACGIH STEL (ppm)
 30,000 ppm

 OSHA
 OSHA PEL (TWA) (mg/m³)
 9,000 mg/m³

 OSHA
 OSHA PEL (ppm)
 5,000 ppm

## 8.2 Advice on system design:

Appropriate engineering controls:

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of the workday.

Maintain air concentration below occupational exposure standards, providing adequate ventilation. Use explosion-proof ventilating equipment.

### 8.3 Personal protective equipment:

### **Respiratory protection:**

If ventilation is insufficient wear suitable respiratory equipment. Select respirator according to estimated exposure levels.

### **Skin protection:**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

## Eye protection:

Safety glasses are always recommended when using chemicals, particularly products that spray.

## **Body protection:**

Wear suitable protective clothes.

camu, Inc. Page 8/16

Revision date: 2020/04/21

Version: 1.2

## General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. No eating, drinking, smoking, or tobacco use at the place of work. Handle in accordance with good industrial hygiene and safety practice.

# Section IX. Physical and chemical properties

Form: liquid.

Odor: characteristic, solvent.

Odor threshold: not applicable.

Color: clear.

pH value: not available Melting point/freezing point: not available.

Boiling point: 132 F (2 Propanone) Flash point: -4 F (2 Propanone)

Flammability: Extremely flammable aerosol.

Lower explosion limit: 2.6% (2 Propanone).

Upper explosion limit: 12.89% (2 Propanone).

Autoignition temperature: no data available.

Vapor pressure: 2.4x104 Pa (2 Propanone)

Density: 0.82 g/cm³@ 75 F. Vapor density: no data available. Partitioning coefficient n- no data available.

octanol/water (low Pow)

Self-ignition temperature no data available.

Thermal decomposition: no decomposition if stored and handled as

prescribed/indicated.

Viscosity, dynamic: no data available.
Viscosity, kinetic: no data available.
Solubility in water: not soluble.

Solubility (quantitative) no data available.
Solubility (qualitative) no data available.

Evaporation rate: value can be approximated from Henry's Law of Constant Vapor

pressure.

Other information: If necessary, information on other physical and chemical

parameters is indicated in this section. No further information is

available.

VOC% <=33%

mu, inc. Page 9/16

Revision date: 2020/04/21

Version: 1.2

## Section X. Stability and reactivity

### 10.1 Reactivity:

No dangerous reaction known under conditions of normal use.

## 10.2 Chemical stability:

Stable under normal conditions. Flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

### 10.3 Possibility of hazardous reactions:

No dangerous reaction known under conditions of normal use.

## 10.4 Conditions to avoid:

Heat, flames, and sparks.

#### 10.5 Incompatible materials:

Strong oxidizing agents.

## 10.6 Hazardous decomposition products:

May include, but not limited, to oxides of carbon and oxides of nitrogen.

# **Section XI. Toxicological information**

## 11.1 Primary routes of exposure:

Routes of entry for solids and liquids are ingestion and inhalation but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Primary routes of entry:

Dermal contact.

Eyes.

Inhalation.

### 11.2 Acute toxicity effects:

Effects are known to the components, not the product as a whole.

Acute toxicity:

Oral:

2 Propanone (67-64-1)
LD50 oral rat 9,570 mg/kg
Methylbenzene (108-88-3)

mu, inc.
Page 10/16

Revision date: 2020/04/21

Version: 1.2

 LD50 oral rat
 5,580 mg/kg

 Heptane
 (142-8-5)

 LD50 Rat
 5,000 mg/kg

 Methyl Alcohol
 (67-56-1)

 LD50 oral rat
 5628 mg/kg

Inhalation:

2 Propanone (67-64-1)

LD50 inhalation rat 50,100 mg/m<sup>3</sup> 8 hours

Methylbenzene (108-88-3)

LC50 inhalation rat 25.7 mg/l 4 hours

Heptane (142-8-5)

LD50 Rat 29.29 mg/l 4 hours

Methyl Alcohol (67-56-1)

LD50 inhalation rat 130.7 mg/l 4 hours

Dermal:

(67-64-1)2 Propanone LD50 dermal rabbit 20,000 mg/kg Methylbenzene (108-88-3)LD50 dermal rabbit >5,000 mg/kg Heptane (142-8-5)LD50 Rabbit 2,000 mg/kg Methyl Alcohol (67-56-1)LD50 dermal rabbit 15,800 mg/kg

<u>Irritation/corrosion:</u>

Not classified.

Eye:

Not classified.

**Respiratory or Skin Sensitization:** 

Not classified.

## 11.2 Chronic toxicity effects:

Repeated dose toxicity:

Skin irritation, eye irritation.

Genetic toxicity:

Not classified.

Carcinogenicity:

Not classified.

Reproductive toxicity:

Page 11/16

Revision date: 2020/04/21

Version: 1.2

Suspected of causing reproductive toxicity to the unborn child.

### Teratogenicity:

Not classified.

### Other information:

The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

## 11.2 Symptom of exposure:

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11. Further symptoms and/or effects are not known so far.

## **Section XII. Ecological information**

## 12.1 Toxicity:

Toxicity is known to the components, not the product as a whole.

### **Ecology General**

No substances are classified as dangerous to the environment according to the criteria of regulation EC No 1272/2008

### **Ecology Air**

No substances included in the list of fluorinated greenhouse gases (regulation EU No 517/2014). Not classified as dangerous to the ozone layer (Regulation EC No 1005/2009).

Ecology water" Toxic to crustacea and fish. Groundwater pollutant. Fouling to shoreline. Inhibits photosynthesis of algae. Harmful to bacteria. Taste alteration in fish and aquatic organisms.

2 Propanone (67-64-1)

Fish LC50 5,540 mg/l 96 h Invertebrates EC50 8,800 mg/l 48 h

Mehylbenzene (108-88-3) Fish LC50 5.5 mg/l 96 h

Heptane (142-8-5) Invertebrates EC50 1.5 mg/l 48 h

Methyl Alcohol (67-56-1)

Fish LC50 19,500-20,700 mg/l 96 h

Sicamu, Inc.
Safety Data Sheet
SQ Non-Chlorinated Brake Cleaner

Page 12/16
Safety Data Sheet

Revision date: 2020/04/21

Version: 1.2

## 12.2 Persistency and degradability:

All components are biodegradable. Mehylbenzene (108-88-3)

Biochemical oxygen demand (BOD):  $2.15 \text{ g/O}_2 \text{ substance}$ Chemical oxygen demand (COD):  $2.52 \text{ g/O}_2 \text{ substance}$ ThOD:  $3.13 \text{ g/O}_2 \text{ substance}$ 

BOD (% of ThOD): 0.69

Heptane (142-8-5)

Biodegradability: Aerobic – exposure time 10 days.

Result 56% readily biodegradable.

Biochemical Oxygen Demand 1,920 mg/g Theoretical Oxygen Demand 3,500 mg/g

Ratio BOD/ThBOD 55%

### 12.3 Bioaccumulative potential:

Mehylbenzene (108-88-3) BCF Fish 1 90 (72 H)

Log Pow 2.73

Bioaccumulative potential Low potential for bioaccumulation (BCF<500)

### 12.4 Mobility in soil:

No data available.

### 12.5 Result of PBT and vPvB assessment:

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted.

### **12.6 Other Adverse effects:**

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Additional ecological: Do not empty into drains. Avoid release to the environment.

# **Section XIII. Disposal considerations**

## 13.1 Waste disposal of substances:

This material must be disposed in accordance with all local, state, provincial, and federal regulations.

The generation of waste should be avoided or minimized whenever possible.

Flammable vapors may accumulate in the container.

Revision date: 2020/04/21

Version: 1.2

## **Section XIV. Transport Information**

## 14.1 Land transport:

**USDOT** 

UN Number UN1950 Class 2.1



Propper shipping name

Other information

Special transport precautions

AEROSOLS, flammable, limited quantity

No supplementary information

Do not handle until safety precautions

have been read and understood.

## 14.2 Sea transport:

**IMDG** 

UN Number UN1950 Class 2.1

Propper shipping name AEROSOLS, flammable, limited quantity

Other information No supplementary information

Special transport precautions Do not handle until safety precautions

have been read and understood.

## 14.3 Air transport:

IATA/ICAO

UN Number UN1950 Class 2.1

Propper shipping name AEROSOLS, flammable, limited quantity

Other information No supplementary information

Special transport precautions Do not handle until safety precautions

have been read and understood.

camu, inc.
Page 14/16

Revision date: 2020/04/21

Version: 1.2

## Section XV. Regulatory information

## 15.1 Federal regulations:

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA title III, Section 302.

SARA 311/312 (Specific toxic chemical listings)

Fire hazard, Acute Health Hazard, Chronic Health Hazard

### SARA 313 Components

Methylbenzene

The following components are subject to reporting levels established by SARA title III, Section 313:

Cas Number	Revision date
108-88-3	2007-07-07

Methyl Alcohol 67-56-1

RCRA (hazardous waste code)

	Cas Number	Waste Code
2 Propanone	67-64-1	U002
Methylbenzene	108-88-6	U220
Methyl Alcohol	67-56-1	U154

TSCA (Toxic Substances Control act)

All the ingredients are listed.

CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act)

	Cas Number	Quantity
2 Propanone	67-64-1	5,000 lbs
Methylbenzene	108-88-6	1,000 lbs
Methyl Alcohol	67-56-1	500 lbs

**US California Proposition 65 – Carcinogens and Reproductive Toxicity (CRT)** This product contains a substance known to the state of California to cause birth defects or other reproductive harm.

Methylbenzene (108-88-6)

US California Proposition 65 – Carcinogens List	No
US California Proposition 65 – Developmental Toxicity	Yes
US California Proposition 65 – Reproductive Toxicity – Female	Yes
US California Proposition 65 – Reproductive Toxicity – Male	No

Maximum allowable dose level (MADL) inhalation 13,000  $\mu g/day$  Maximum allowable dose level (MADL) oral 7,000  $\mu g/day$ 

Methyl Alcohol (67-56-1)

mu, inc.
Page 15/16

Revision date: 2020/04/21

Version: 1.2

US California Proposition 65 – Carcinogens List

US California Proposition 65 – Developmental Toxicity

Yes

US California Proposition 65 – Reproductive Toxicity – Female

US California Proposition 65 – Reproductive Toxicity – Male

No

Maximum allowable dose level (MADL) inhalation 47,000  $\mu$ g/day Maximum allowable dose level (MADL) oral 23,000  $\mu$ g/day

## **US States Right to know:**

Massachusetts

2 Propanone (67-64-1)

Methylbenzene (108-88-3)

Methyl Alcohol (67-56-1)

Carbon Dioxide (124-38-9)

**New York** 

2 Propanone (67-64-1)

Methylbenzene (108-88-3)

Methyl Alcohol (67-56-1)

**New Jersey** 

2 Propanone (67-64-1)

Methylbenzene (108-88-3)

Methyl Alcohol (67-56-1)

Carbon Dioxide (124-38-9)

Pennsylvania

2 Propanone (67-64-1)

Methylbenzene (108-88-3)

Methyl Alcohol (67-56-1)

Carbon Dioxide (124-38-9)

**NFPA Hazard Codes:** 

Health: 2 Fire: 3 Reactivity: 0 Special:

## Section XVI. Other information

### SDS Prepared by:

Revision date: 2020/04/21

Version: 1.2

Sicamu.

SDS prepared on: 2020/04/21.

We value the health and safety or our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

While the descriptions, designs, data, and information contained herein are presented in good faith and believed to be accurate, it is provided for your guidance only. Many factors may affect processing or application/use, we recommend that you make tests to determine the stability of a product for your particular purpose prior to use. No warranties of any kind, either expressed or implied, including warranties of merchantability or fitness for a particular purpose are made regarding products described or designs, data or information set forth, or that the products, designs, data, or information may be used without infringing the intellectual property rights of others. In no case shall the descriptions, information, data, or designs provided be considered a part of our terms and conditions of sale. Further, you expressly understand and agree that the description, designs data and information furnished hereunder are given freely and we assume no obligation or liability for the description, design, data, and information given or results obtained, all such being given and accepted at your risk.