





# I. PRODUCT IDENTIFICATION

Manufacturer:	WD-40 Company	Telephone: Emergency Only:	1 (800) 424-9300
Address:	1061 Cudahy Place (92110) P.O. Box 80607 San Diego, California 92138-0607	Information: Chemical Name: Trade Name:	(CHEMTREC) (619) 275-1400 Organic Mixture Three-In-One Multi-Purpose Oil

#### **II. HAZARDOUS INGREDIENTS**

Chemical Name	CAS Number	%	Exposure Limit ACGIH/OSHA
Severely Hydrotreated Heavy Naphthenic Oil	64742-52-5	> 97	5 mg/M³ TWA (mist)
Non-hazardous Ingredients		< 3	

# **III. PHYSICAL DATA**

Appearance:	Clear amber liquid	Volatiles:	Nil
Odor:	Faint citronella	pH:	Not applicable
Boiling Point:	Above 550°F	Specific Gravity:	0.886 - 0.923 @ 20°C
Freezing Point:	Not applicable	Vapor Pressure:	Not determined
Solubility in Water:	Insoluble	Vapor Density (Air = 1):	Not determined

# **IV. FIRE AND EXPLOSION**

Flash Point:	Above 305°F TOC
Flame Extension:	Not applicable
Extinguishing Media:	CO <sub>2</sub> , Dry Chemical, Foam, Water Spray
Fire Fighting Procedures:	Use water to keep fire-exposed containers cool.

# V. HEALTH HAZARD / ROUTE(S) OF ENTRY

Symptoms of Overexposure Inhalation (Breathing): Skin Contact: Eye Contact: Ingestion (Swallowed):	May cause anesthesia, headache, dizziness, nausea and upper respiratory irritation. May cause drying of skin and/or irritation. May cause irritation, tearing and redness. May cause irritation, nausea, vomiting and diarrhea.
First Aid Procedures Ingestion (Swallowed): Eye Contact: Skin Contact: Inhalation (Breathing):	Do not induce vomiting. Seek medical attention. Immediately flush eyes with large amounts of water for 15 minutes. Wash with soap and water. Remove to fresh air. Give artificial respiration if necessary. If breathing is difficult, give oxygen.
DANGER! Aspiration Hazard:	If swallowed, can enter lungs and may cause chemical pneumonitis. Do not induce vomiting. Call Physician immediately.
Suspected Cancer Agent Yes Nox	The components in this mixture have been found to be noncarcinogenic by NTP, IARC and OSHA.

# **VI. REACTIVITY DATA**

Stable <u>x</u>	Unstable	
NA		
Strong oxidizing materials		
Thermal decomposition may yield carbon monoxide and/or carbon dioxide.		
May occur	Will not occur <u>X</u>	
	NA Strong oxidizing materials Thermal decomposition m	

# **VII. SPILL OR LEAK PROCEDURES**

#### **Spill Response Procedures**

Absorb small quantities with sand, earth, sawdust. Large quantities pump into tank.

# Waste Disposal Method

Incinerate liquid, bury saturated absorbent in land fill. Dispose of in accordance with local, state and federal regulations.

#### **VIII. SPECIAL HANDLING INFORMATION**

Ventilation Requirements:	Use local exhaust to capture vapor, mists or fumes, if necessary. Provide ventilation sufficient to prevent exceeding recommended exposure limit or build-up of explosive concentrations of vapor in air. No smoking, or use of flame or other ignition sources.
Respiratory Protection:	Use air respiratory protection in confined or enclosed spaces, if needed.
Protective Gloves:	Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.
Eye Protection:	Use splash goggles or face shield when eye contact may occur.

#### **IX. SPECIAL PRECAUTIONS**

Keep from open flame. Do not take internally. Avoid excessive inhalation of vapors. Keep from children.

# X. REGULATORY INFORMATION

All ingredients for this product SARA Title III chemicals: California Prop 65 chemicals: CERCLA reportable quantity: RCRA hazardous waste no.:				
SIGNATURE: R. Miles	Zhiles	TITLE:	Technical	Director
REVISION DATE:	February 2003	SUPERSEDES:	Februar	ry 2000
NA = Not applicable	NDA = No data available	< = Le	ss than	> = More than

We believe the statements, technical information and recommendations contained herein are reliable. However, the data is provided without warranty, expressed or implied. It is the user's responsibility both to determine safe conditions for use of this product and assume loss, damage or expense, direct or consequential, arising from its use. Before using product, read label. MSDS 3/B