



## **RENOVATORS SUPPLY MANUFACTURING**

**Antique Reproduction & Modern Hardware Sinks and Toilets**

*By The Renovators Supply, Inc. - The Most Trusted Source Since 1978*

Customer Service: 1-800-659-2211 or International:1-413-423-3300

E-Mail ID: [cs@rensup.com](mailto:cs@rensup.com)

### **Drop-In-Sink**



Note: Please read the installation and maintenance instructions thoroughly. Assess your sink for any observable damage before installation. Large sinks are heavy, get help lifting the sink.

To install a drop-in sink, you will need a cutout on the countertop made. If you don't know what you are doing aren't sure how to make the cutout, please seek the guidance of someone who could help you out. Lift and place the sink and place it on the cutout of the countertop. The dimensions of the sink rim must connect exactly with the counter when the sink is being installed. Platform must be able to bear the heaviness of the sink and any parts. At the point when the sink is put onto a platform, ensure the top of the sink is equally flush against the base of the counter-top.

Set the sink on top of the countertop. Apply Sealant/Caulk right around the gap in the countertop where the rim/edge of the sink will sit. When you have caulked right around the gap you would then be able to put the sink into the opening. When you have positioned the sink appropriately, you would then be able to apply caulk right around the edge between the sink and the countertop. When you have your caulking right around your sink you will need to ensure every corner of the sink is in the ideal position

When you have verified that your sink is perfectly installed you would then be able to further do the fixture installations into place and tidy up any additional caulk which is on the counter.

For more info, contact Customer Service: 1-800-659-2211 or International:1-413-423-3300

E-Mail ID: [cs@rensup.com](mailto:cs@rensup.com)

